Sanitized Copy Approved for Release 2010/05/04 : CIA-RDP80T00246A032500030001-7

PROCESSING COPY

CENTRAL INTELLIGENCE AGENCY

This material contains information affecting the National Defense of the United States within the meaning of the Espionage Laws, Title 18, U.S.C. Secs. 783 and 794, the transmission or revelation of which in any manner to an unauthorised person is prohibited by law.

| | | ENCLOSURE ATTACHE | D -R | | 25 X 1 |
|---------|-----------------|---------------------------------|-------------------------|---|---------------|
| COUNTI | Y Poland | PLEASE ROUTE | REPORT | | |
| SUBJECT | Poliish | Iron and Steel Production | DATE DISTR. | 4 February 1957 | |
| | | | NO. OF PAGE | s | |
| DATÉ O | F INFO. | | REQUIREMENT | NO. RD | 05)// |
| PLACE / | ACQUIRED | | REFERENCES | | 25 X 1 |
| DATE A | CQUIRED | | | | |
| | S | DURCE EVALUATIONS ARE DEFINITIV | E. APPRAISAL OF CONTENT | IS TENTATIVE. | |
| | | | | | 25) |
| | | | | | - J. F |
| | and stee | production in Poland. | four repo | rts dealing with iron | I/195 |
| | | - programment in rotality. | | | - |
| | a. Raw 1 | Materials for the Polish I | ron and Steel Industry | Polish Coke Plants | till 1 |
| | b. Coke | Plant in Poland (Suppleme | nt to a.above) (1 page | | 1 |
| | c. Polis | sh Iron Production (2 page | s) | 12 MAR 4 | 501 W |
| | d. Polis | sh Steel Production (3 page | es) | CONTRACTOR OF THE PARTY OF THE | 957 |
| | • | <u> </u> | | | 25X |
| | | | | 1 6 AFG | |
| | | | | *** | |
| | | | | Tarani. | |
| | | | | | |
| | | | | | C/I |
| | | | | | |
| | | | | | |
| | | | | . 4 | |

S-E-C-R-E-T

| | STATE | X | ARMY | х | NAVY | X | AiR | x | _ PI | N | ┸ | AEC | | | 1 | 1 | ~ |
|---|-------|---|------|---|------|---|-----|----------|------|---------|-------------|-------------|----------------|----------|-------|--------------|----------|
| | | | | | - 7 | | 4 2 | (Nei | Mr W | unbing) | on d | Hetribution | indicate | l by "X" | Field | distribution | by "#".) |
| • | | | | | 17 | | T. | s Prince | | | | | | | | | |
| | | | | | | | | | | | | | | | | | |
| 7 | | | | | | | | - | - | | - 17 | ئەنقەد . سە | A Marketon and | | | +11 | |

Sanitized Copy Approved for Release 2010/05/04 : CIA-RDP80T00246A032500030001-7

25X1

社し

| | | | | I non and | | | |
|----------|-----|-----------|-----|--------------|-----------|----------|--|
| SUBJECT: | Raw | Materials | for | Polish Steel | Industry, | | |
| | | • • | | • | - 1 | <i>!</i> | |
| | | | | | | | |

1. Lime: There are enough lime deposits in Poland to supply not only the Polish Iron and steel industry but also other industrial needs and the meds of agriculture. The best deposits are in the Czajkow/Krakow arms, in Czrzanow/
Krakow, Zabkowice and Grodziec-Saturn /Sossnowitz, Kielce/150 km from Warsaw, and
Nikalaiken/Upper Silesia, Naklo/Upper Silesia, Tarnowitz,/Groszowice/Oppelmit areas. These lime deposits are large enough to innk meet Polish industrial needs for hundreds of years. In addition to these deposits, other smaller it deposits can also be tapped. The same situation exists in the cement industry, the with the best cement being produced in Czajkow/Krakow, Grodziec, and the production Groszowice areas. The Czajkow cement is exported and/is allegedly sold out for years to come. In conclusion, Poland will not suffer a lack of lime, cement, or dolomite for hundreds in the cament industry.

2. Iron Ore: The low grade iron ore deposits in Poland are not sufficient even to meet the needs of its heavy industry. There are limonite (bog iron) deposits in Kielce with an iron content of 25 to 37 percents and in the Tarnobitz area with an iron content of from 25 to 30 percent. Small deposits of pyrites with an iron content of 44 percent are located in the Radom area about 4 to 5 meters underground; the recovery is expensive and unprofitable. Thus, all good iron ore for the Polish iron and steel industry must be imported. The ore currently comes from and from Krivoy Rog/Dnepropetrovsk USSR. There are minumed small deposits of quarzite for production of silica material for Siemens-Martin

open hearth furnaces in the Parzynow/Posen area.

usually

3. Coke: Coke plants in Poland/are supplied with coal from their own mines, with

3. Coke: Coke plants in Poland/are supplied with coal from their own mines, with various types of coal being mixed dependent on the type of coke being produced. A list of Polish coke plants and production capacities is submitted below:

Sanitized Copy Approved for Release 2010/05/04: CIA-RDP80T00246A032500030001-7

25X1

25X1

This plant,
formerly called the "Emmagrube", former owner Friedlaenderfuld,

was constructed in 1930 by the "Dr. Otto und Co." firm of Bochum,

Germany. There are four batteries each with 55 chambers. The

chambers are .46 meters x 2.8 meters x 11.70 meters. The capacity

of the plant is 2,000 tons of high grade blast furnace and

twenty four hours.

foundary coke made from 2,700 tons of coal in Enchanges Engagements

Manual Scholar Malay and Market Marke

separation of by-products such as gamy ammonia, maintain, benzene,

Facilities are available for

and tar.

Dubensko Coke Plantita Rybnik; This plant was constructed in 1933. Two batteries each were with 55 chambers was built by the "Dr. Otto und Co." firm of Bochum and has the chambers have the dimmensions listed above. These batteries produce a total of 1,000 tons of high grade foundary coke from 1,400 tons of coal in twenty four hours. Two batteries of 50 chambers each were built by the "Firma Koppers" of Essen, Germany. The chambers are .38 meters x 3.40 meters x 11.00 meters and produce influence and produce in twenty four hours. Total capacity of the plant is thus 1,910 tons in twenty four hours. Facilities are available for separation and commercial production of tar and benzene.

Kokerei Wolfgang near Ruda: The formmer owner the "Graf Ballestremsche Gruben"

complex. It was constructed in 1931 by the "Dr. Otto und Co."

firm of Bochum and consists of four batteries each of 55

chambers. The dimmensions of the chambers are as given above.

Total capacity of the plant is 2,000 tons of household coke from 2,700 tons of coal in twenty four hours. No foundary coke is produced. Facilities are available for commercial production of

Sanitized Copy Approved for Release 2010/05/04: CIA-RDP80T00246A032500030001-7

SECRET

benzene, tar, and ammonia. Gas from this plant incumination used

Ex commercially in the surrounding areas.

Falwahuette near Kattowitz: This is plant manufarmed kanama in the manufarmed kanama in the manufarmed kanama in the manufarmed kanama kanama in the manufarmed kanama kan

Hubertushuette near Beuthen: This plant was built by the "Firma Colling" of Germany
in 1918. The chambers are .50 meters k x 2.20 meters x 10 meter

grade household coke from 1010 tons of coal in twenty four hours. It does not produce foundary coke and no facilities are available for separation of by-products.

Knurow Plant near Gleiwitz: This plant was built in 1936 by the ## #Bik "Distikoks"

firm of Paris. It has two batteries each with 55 chambers. The

chambers are .45 x khriffinx 2.80 x 11.75 meters. The plant

can produce 1,000 tons of good foundary coke from 1,350

tons of coal in twenty four hours. There are no facilities

available for separation of by-products.

Gleiwitzerhuette near Gleiwitz: This plant was built in 1939. Imm Three batteries

each of 35 chambers were built by the "Dr. Otto und Co."

firm; dimmensions of the chambers are as given above. Two

batteries each of 35 chambers were built by the "Firma

Still" in Recklinghausen, Germany; dimmensions of the chambers

SECPr-

are .34 x 3.50 x 11.00 meters. Capacity of all five batteries in twenty four hours is 1,700 tons of good foundary coke from 2,430 tons of coal. Separation facilities for by-products are available.

Now House Huta near Krakow: This plant was built in 1954 by the "Dr. Otto und Co. "

December 1956 firm of Germany. It has two batteries each with 55 chambers.

Dimmensions of the chambers are as above. Capacity of the plant is 1,000 tons of foundary coke from 1,350 toms of coal in twenty four hours. There are no separation facilities for by-products.

by the "Firma Collin" in, Germany. It consists of four batteries each of 40 chambers using the old system. Dimmensions of the chambers are as listed above. Capacity of the plant in twenty four hours is 1,500 tons of household coke from about 2,000m.

No foundary coke is produced.

tons of coal./ No facilities are available for separation of by-products.

Kokanstalt Donnersmark: Theaplant was built about 1924 by the "Firma Collin". It has four batteries each with 35 chambers of the old system. It can produce 1,300 tons of household coke from 1,850 tons of coal. No foundary coke is produced. Separation facilities are available for by-products.

Julianhuette near Bobrek: The plant was built about 1933. Two batteries each with

35 chambers were built by the "Firma Still" of Recklinghausen;

dimmensions are as above. Two batteries each with 35 chambers

were built by the "Dr. Otto und Co." firm; dimmensions are as

above. Total capacity of the four batteries is 1,360 tons of

SECR --

good foundary coke from 2,000 tons of coal in twenty four hours. Separation facilities for by-products are available and from the plant gas/is used commercially in the area.

Kokersibetriab Graf Schafgotsch: This plant, with administrative headquarters in Gleiwitz, was built in 1935 by the "Firma Still". It has four batteries each with 55 chambers. Dimmensions of the chambers are as above. It can produce 2,000 tons of good foundary coke from 2,700 tons of coal in twenty four hours. Facilities are available for commercial production of by-products and gas from the plant is used commercially in the area.

Sanitized Copy Approved for Release 2010/05/04 : CIA-RDP80T00246A032500030001-7

d

SUBJECT: Polish Steel Production

25X1

- 1. The following steel producing furnaces are located in Poland at the installations listed; capacities for each of the furnaces is as noted:
- a. Falwahuette in Schwientochlowitz: This foundary has two Siemens-Martin furnaces wach with a capacity of 150 tons per charge. It also has two Siemens-Martin furnaces with each with a 100 ton capacity and one Siemens-Martin with a capacity of 40 tonsx per charge. All furnaces can be charged three times in 24 hours, enabling a theoretical capacity of 1,620 tons for the foundary for 24 hours.
- b. Bismarkhuette-Unterwerk: The foundary has two Siemens- artin furnaces each with a 40 ton per charge capacity. Total theoretical capacity is thus 240 tons in 24 hours.
- c. Friedenshuette (Huta Pokoj): The foundary has two Siemens-Martin furnaces each with a 100 ton per charge capacity and two with each having 40 ton capacity, enabling a 24 hour capacity of 840 tons.
- d. Baildonhuette near Kattowitz: The foundary has three Siemens-Martin furnaces each with a 40 ton per charge capacity and one 20 ton per charge Siemens-Martin furnace. Total capacity for 24 hours is 420 toms.
- e. Laurahuette near Semianowitz: The foundary has three Siemens-Martin furnaces each with a 40 ton per charge capacity. Total foundary capacity is 360 tons for 24 hours.
- f. Huta Pilsudskiego in "oenigshuette: The foundary has two Siemens-Martin furnaces each with a 100 ton per charge capacity and two 40 ton per charge Siemens-Martin furnaces. Total 24 hour capacity is 840 tons.
- g.Julienhuette in Bobrek: The foundary has three 100 ton per charge Siemens-Martin furnaces and two 40 ton per charge Siemens-Martins. hydra Total 24 hour capacity is 1,140 tons.

SECRET

- h. Huettenwerk Zawadzki in Zawadzki/Malapane: The foundary has three 40 ton per charge Siemens-martin furnaces made emabling a 24 hour capacity of 360 tons.
- i. Huettenwerk Borsigwerk near Beuthen: The foundary has two Siemens-Martin furnaces each with a 100 ton per charge capacity and two Siemans Martins with a 40 ton per charge capacity. Total 24 hour capacity is 840 tons.
- j. Hubertushuette near Beuthen: The foundary has two puddling furnaces each with a capacity of 20 tons per charge, enabling a 24 hour capacity of 120 tons.
- k. Donnersmarkhuette in Hindenburg: The foundary has 1 20 ton per charge Siemens-martin furnace ehabling a 24 hour capacity of 60 tons.
- 1. Gleiwitzerhuette near Gleiwitz: The foundary has one 20 ton per charge Siemens-Martin furnace enabling a capacity of 60 tons.
- m. Huta Bankowa in Sosnowitz: The foundary has three Venturi furnaces each with a loo tom per charge capacity and two Venturi furnaces mixin each with a 40 ton capacity, enabling a 24 hour capacity of 1,140 tons.
- n. Huta Modrzow Hantke waxes transference. The foundary has one iemens—Martin furnace with a 20 ton per charge capacity, enabling a capacity of 60 tons in 24 hours.
- o. Huta Zawierce in Warthenau The foundary has three Siemens-wartin furnaces each with a kpkm 40 ton per charge capacity, enabling a capacity of 360 tons in 24 hours.
- p. Huta Hultschinski in Sosnowitz: The foundary has markapa one Schemens-Martin furnace with a capacity of 40 tons per charge, enabling a 24 hour capacity of 120 tons.
- q. Huta Mordzow-Hantke near Czenstochau: The foundary has two Siemens-Martin furnaces each with a capacity of 40 tons per charge and two Siemens-Martins each with a 20 ton per charge capacity. Total 24 hour capacity is 360 tons.

- r. Huta Stalowawola near Krakow: The foundary has four Siemens-Martin each furnaces/with a 100 ton per charge capacity and one Siemens-Martin furnace with a 40 ton per charge capacity. Total capacity for 24 hours is 1,320 tons.

 Nowa Huta near Krakow: The foundary has three Siemens-Martin furnaces each with a capacity of 300 tons per charge, enabling a total 24 hour capacity of 2,700 tons.
 - t. Private Foundary in Warthenau-Zawierce: This foundary has two Siemens-Martin furnaces each with a 20 ton per charge capacity, enabling a 24 hours capacity of 120 tons.
 - 2. Total theoretical capacity for the Polish steel industry for 24 hours is approximately in 13,080 tons, which amounts to a yearly capacity of frameworks four and one half million tons. With good production techniques and planning, the Polish steel industry can reach this capacity.

25X1

* C

SECRET

SUBJECT: Polish Iron Production

1. There are 27 blast furnaces located in Poland at the following installations; capacities for each of the furnaces are as listed:

- a. Huta Pilsudskiego in Koenigshuette: The plant has one modern blast furnace with a capacity of 840 tons in 24 hours. It also has three bakast furnaces of old style wakkex each with a capacity of 100 tons in 24 hours. Total 24 hour capacity of the plant is 1,140 tons.
- b. Falwahuette in Schwientochlowitz: The plant has twom furnaces of old style each with a capacity of 80 tons per two 24 hours. Total 24 hour capacity of the plant is 160 tons.
- c. Friedenshuette near Beuthen: The plant has three ballst furnaces of old style each with a capacity of 150 tons in 24 hours. Total plant capacity for 24 hours is 450 tons.
- d. Laurahuette near Semianowitz: The plant has two furnaces of old style each with a capacity of 100 tons in 24 hours. Total 24 hours capacity is 200 tons.
- e. Julienhuette near Bobrek: The plant has keen renovated blast furnaces each with a capacity of 200 tons in 24 hours. Total 24 hour capacity is 600 tons.
- f. Donnersmarkhuette mann in Hindenburg: The plant has three furnaces of old style each with a capacity of 100 tons in 24 hours. Total 24 hour capacity is 300 tons.
- g. Huta Bankowa in Sosnowitz: The plant has three furnaces of old style each with a capacity of 200 tons in 24 hours. Total 24 hour capacity is 600 tons.
- h. Huta Modrzow Hantke near Czenstochou: The plant has two furnaces of old style each with a capacity of 80 tons in 24 hours. Total 24 hour capacity is 160 tons.
- 1. Nowa Huta near Krakow: The plant has three new blast furnaces each with a capacity of 300 tons in 24 hours. Total 24 hour capacity is 900 tons.

25X1


m. Huta Zawierce in Warthenau: The plant, which has its own iron supply with about 30 percent iron content, has two furnaces of old style each with a capacity of 100 tons for 24 hours. Total 24 hour capacity is 200 tons.

2. Although total Polish iron production could reach a capacity of 4,710 tons in 24 hours, the capacities given above are theoretical only. As a result of bad planning and production techniques, the actual production amounts to only from 2,500 to 3,000 tons in a 24 hour period. The igner walls of the furnaces must be replaced after a life of approximately 400 charges. The charges usually last about six and one balk hours but the furnaces can be charged only three times in 24 hours. To produce the real sepacity of 2,500 tons in 24 hours, a mixture of 250 tons of lime, 230 tons of foundary coke, 750 tons of processed scrap, 750 tons of unprocessed scrap, 500 tons of low grade iron ore, and 740 tons of high grade ore would be utilized.

| Sai | nitized Copy A | pproved for Release 2010/05/04 : CIA-RDP | 80T00246A032500030001-7 | 25 X 1 |
|----------|----------------|--|-------------------------|---------------|
| SUBJECT: | Supplement | | | 25X1 |
| | | | | 25X1 |
| | | | | |

Xiinnen migha nikakumarkun ixiinnikin nimakan meganxiiinin makumakuma men makumakan in kuri 1915 in

Vereinigte Kokswerke in Borsigwerk near Beuthen: This plant was constructed in the period 1935-1936 by the "Firma Still" of Recklinghausen and the "Firma Koppers" of Essen. It consists of three batteries each having fifty chambers. Dimmensions of the chambers are 2.80 meters x .45 meters x 11.50 meters. The plant can produce 2,700 tons of foundary coke from 3,500 tons of coal in twenty four hours. Facilities are available for separation of by products such as tar and benzine.



Sanitized Copy Approved for Release 2010/05/04: CIA-RDP80T00246A032500030001-7